Karta zastosowań

Zastosowanie

NANOQUICK® Modern Nanotechnology System	NANOQUICK® BETON	NANOQUICK® BRUK	NANOQUICK® BRUK GRANIT	NANOQUICK® BRUK P	NANOQUICK® BRUK WET	NANOQUICK® BRUK & BETON REPAIR	NANOQUICK® PIASKOWIEC	NANOQUICK® PIASKOWIEC REPAIR	NANOQUICK® PIASKOWIEC FROST	NANOQUICK® MINERAL	NANOQUICK® MINERAL HD	NANOQUICK® MINERAL WET	NANOQUICK® MINERAL REPAIR	NANOQUICK® MINERAL FROST	NANOQUICK® CERAMIKA OIL	NANOQUICK® CERAMIKA HD	NANOQUICK® CERAMIKA HDR	NANOQUICK® GIPSUM	NANOQUICK® GRESUM	NANOQUICK® GRESUM HD	NANOQUICK® FUGA	NANOQUICK® GLASS	NANOQUICK® PEBBLES WHITE	NANOQUICK® GNEJS	NANOQUICK® GNEJS WET	NANOQUICK® DREWNO	NANOQUICK® BRUK+	NANOQUICK® BRUK W+	NANOQUICK® CERAMIKA+	NANOQUICK® CERAMIKA W+	NANOQUICK® MINERAL+	NANOQUICK® FUGA+	NANOQUICK® GLASS+	NANOQUICK® GNEJS+	NANOQUICK® ANTIALG+
Chłonność materiałowa																																					
Niskochłonne	■		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Chłonne	●	●	■	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●	●	●	●	●
Materiały																																				
Wyroby betonowe, prefabrykanty	●		■	●	●	●	■		■		■		■		■		■			■		■		■				●	●	■		■		■		●
Kostka brukowa	■	●	■	●	●	●	■		■		■		■		■		■			■		■		■				●	●	■		■		■		●
Kostka granitowa, granity	■		●		■		■		■		■	●	●	●	■		■			■		■		■						■		■		■		●
Piaskowiec kwarcowy, arkazowy	■		■		■		●	●	●		■	●	●	●	■		■			■		■		■						■		■		■		●
Piaskowiec szarogłazowy	■		■		■		●	●	●		■	●	●	●	■		■			■		■		■	●					■		■		■	●	●
Wapień	■		■		■		■		■	●	●	●	●	●	■		■			■		■		■	●					■		■		■	●	●
Marmur	■		■		■		■		■	●	●	●	●	●	■		■			■		■		■	●					■		■		■	●	●
Granit	■		●		■		■		■		●	●	●	●	■		■			■		■		■	●					■		■		■	●	●
Trawertyn	■		■		■		■		■	●	●	●	●	●	■		■			■		■		■	●	●				■		■		■	●	●
Gnejs	■		■		■		■		■	●	●	●	●	●	■		■			■	●	■		■	●	●				■		■		■	●	●
Łupki	■		■		■		■		■	●	●	●	●	●	■		■			■	●	■		■	●	●				■		■		■	●	●
Szkło i elementy szklane	■		■		■		■		■		■		■		■		■			■		■	●	■		■				■		■		■	●	■
Ceramika, klinkiery, dachówki	■		■		■		■		■		■		■		●		■			■		■		■		■				■	●	■		■		●
Ceramika, gresy, płytki	■		■		■		■		■		●	●	●	●	■	●	●			■	●	■		■		■				■		■		■		■
Fugi mineralne	■		■		■		■		■		■	●	●	●	■	●	●			■		●		■		■				■		■	●	■	●	■
Drewno surowe	■		■		■		■		■		■		■		■		■			■		■		■		■	●			■		■		■		●
Wyroby gipsowe	■		■		■		■		■		■		■		■		■	●		■		■		■		■				■		■		■		●
Inne powierzchnie mineralne (zlepieniec, ortokwarcyt, kreda, dolomit, margiel, bazalt, gnejs, kwarcyt, onyks)	■		■		■		■		■		●	●	●	●	■		■			■		■		■	●	●				■		■		■	●	●
Wyroby otoczone białe (Włochy, Macedonia, Grecja, Turcja)	■		■		■		■		■		■		■	●	■		■			■		■		●		■				■		■		■	●	●
Informacje dodatkowe																																				
Dodatek do masy	■		■		■		■		■		■		■		■		■			■		■		■		■				■		■		■		■
Do powierzchni szkliwionych, szlifowanych	■		■		■		■		■		■		■		■		■			■		■		■		■				■		■		■		■

Temperatury pracy

Temperatury przechowywania																																				
max 30° C	■		■		●		■		■	●	●		■	●	■		■			■		●		■		●			■		■		■		■		■
max 35° C	●	●	●	●		●	●	●	●		■	●	●		●	●	●	●	●	●	●		●	●		●	●	●	●	●	●	●	●	●	●	●
min 2° C	●	●	●	●	●	●	●	●	■	●	■	●	●		●		■	●	■		●		●	●	●	●	●	●	●	●	●	●	●	●	●
min -5° C	■		■		■				●		●		■	●	■	●	●		●	●		●		●												
Temperatury materiału (przy nakładaniu)																																				
max 55° C	●		■	●		●		●	●		●	●	●	●		●	●			■		■	●		■			■		■		■		■		■
max 40° C	■		●		●		●		■	●	■		■		●		■	●	●	●	●		●	●	●	●	●	●	●	●	●	●	●	●	●

Właściwości

Magazynowanie / czas przechowywania																																				
24 miesiące	■		■		■		■		■		■		■		■		■			■		■		■		■				■		■		■		■
36 miesięcy	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Właściwości chemiczne																																				
palność	■		■		●		■		■		●	●			■	●	●		●	●		●			●			■		■		■		■		■